



Fitting Instructions –  
Mazda MIATA MX5 Mk4 Half Cover 2015 Onwards (262)  
/ Fiat 124 Spider 2016 Onwards

**Please note; prior to each installation ensure the area where the roof protector meets the vehicle paintwork is thoroughly clean, and the corresponding areas on the cover are cleared of any debris.**

1. Flip up your wiper blades and carefully place the cover in approximate position over your soft top.
2. Open each door slightly, and insert the short padded ribs on either side inside the front and rear openings of each door. Gently close the doors trapping the material inside. (Figure 1 shows rib locations on a typical roof protector)
3. Attach the Velcro closure around the wing mirrors.
4. Place the wipers over the cover on the windscreen.
5. Open the trunk and align the padded rib (or ribs, depending on model) inside the trunk. Carefully close the trunk lid, trapping the ribs inside (Figure 2 shows an example).



Figure 1



Figure 2



The cover is waterproof and designed to protect your soft top whilst the car is parked, however we do not recommend long term use without removing the cover periodically to air your soft top, and reduce condensation build up.

### **Soft Top Roof Protector Maintenance**

The weather is unpredictable and harsh on anything fabric! Regular cleaning and maintenance of your fabric roof protector is as easy as washing your car, and will help to preserve its colour and water-proofing ability.

This is no different than the process for cleaning/maintaining your soft top. If you are not familiar with this process there are some great resources online, but it is basically a two-step process as follows:

Firstly, use a gentle car shampoo, such as RaggTopp Fabric/Vinyl Cleaner, which is safe for use on both fabric and vinyl tops. The formula lifts soils and stains, and will repel the growth of mildew, as well as repel future stains from other sources.

Secondly, use a protectant, such as RaggTopp Fabric Protectant, which will protect your top from acid rain, along with U.V. rays, smog, tree sap, bird droppings, salt, tar, dirt, grease, and grit. It contains UV stabilizers and is ozone-friendly.

Be sure to apply protectant to a clean, dry top. Never saturate; light, even coats are always best. Reapply monthly to maintain an optimum level of water repellency.